



330W PERC Half-Cell Module

JAM60S03 310-330/PR Series

Introduction

Assembled with high-efficiency PERC cells, the half-cell configuration of the modules offers the advantages of higher power output, better temperature-dependent performance, reduced shading effect on the energy generation, lower risk of hot spot, as well as enhanced tolerance for mechanical loading.



Higher output power



Lower temperature coefficient




Less shading effect



Better mechanical loading tolerance

Superior Warranty

- 12-year product warranty
- 25-year linear power output warranty




■ JA Linear Power Warranty ■ Industry Warranty

Comprehensive Certificates

- IEC 61215, IEC 61730, IEC TS 62804
- ISO 9001: 2015 Quality management systems
- ISO 14001: 2015 Environmental management systems
- OHSAS 18001: 2007 Occupational health and safety management systems
- IEC TS 62941: 2016 Terrestrial photovoltaic (PV) modules – Guidelines for increased confidence in PV module design qualification and type approval



MECHANICAL DIAGRAMS



Remark: JA standard cable length is 400/300mm, customized frame color and cable length available upon request.

SPECIFICATIONS

Cell	Mono
Weight	18.5kg±3%
Dimensions	1678mm×991mm×35mm
Cable Cross Section Size	4mm ²
No. of cells	120(6×20)
Junction Box	IP68, 3 diodes
Connector	MC4 Compatible(1000V) QC 4.10-35(1500V)
Packaging Configuration	30 Per Pallet

ELECTRICAL PARAMETERS AT STC

TYPE	JAM60S03 -310/PR	JAM60S03 -315/PR	JAM60S03 -320/PR	JAM60S03 -325/PR	JAM60S03 -330/PR
Rated Maximum Power(P _{max}) [W]	310	315	320	325	330
Open Circuit Voltage(V _{oc}) [V]	39.61	39.93	40.22	40.56	40.84
Maximum Power Voltage(V _{mp}) [V]	32.78	33.07	33.34	33.65	33.91
Short Circuit Current(I _{sc}) [A]	10.03	10.10	10.16	10.22	10.29
Maximum Power Current(I _{mp}) [A]	9.46	9.53	9.60	9.66	9.74
Module Efficiency [%]	18.6	18.9	19.2	19.5	19.8
Power Tolerance	0~+5W				
Temperature Coefficient of I _{sc} (α _{Isc})	+0.051%/°C				
Temperature Coefficient of V _{oc} (β _{Voc})	-0.289%/°C				
Temperature Coefficient of P _{max} (γ _{Pmp})	-0.360%/°C				
STC	Irradiance 1000W/m ² , cell temperature 25°C, AM1.5G				


Remark: Electrical data in this catalog do not refer to a single module and they are not part of the offer. They only serve for comparison among different module types.

ELECTRICAL PARAMETERS AT NOCT


TYPE	JAM60S03 -310/PR	JAM60S03 -315/PR	JAM60S03 -320/PR	JAM60S03 -325/PR	JAM60S03 -330/PR	OPERATING CONDITIONS	
Rated Max Power(P _{max}) [W]	229	233	237	241	244	Maximum System Voltage	1000V/1500V DC(IEC)
Open Circuit Voltage(V _{oc}) [V]	36.61	36.93	37.15	37.38	37.65	Operating Temperature	-40°C~+85°C
Max Power Voltage(V _{mp}) [V]	32.77	33.06	33.31	33.54	33.82	Maximum Series Fuse	20A
Short Circuit Current(I _{sc}) [A]	8.02	8.08	8.14	8.20	8.25	Maximum Static Load, Front	5400Pa
Max Power Current(I _{mp}) [A]	7.00	7.05	7.11	7.17	7.22	Maximum Static Load, Back	2400Pa
NOCT	Irradiance 800W/m ² , ambient temperature 20°C, wind speed 1m/s, AM1.5G					NOCT	45±2°C
						Application Class	Class A

CHARACTERISTICS

Current-Voltage Curve JAM60S03-310/PR



Power-Voltage Curve JAM60S03-310/PR



Current-Voltage Curve JAM60S03-310/PR

