



1.Structure Description




1	Body of the connector	2	(5)	Claw	2
2	Metal terminal	2	6	Back cover	2
3	Support sleeve	2	7	Heat-shrinkable sleeve	2
4	Sealing gasket	2			

2. Put the heat-shrinkable sleeve, back cover, claw and sealing gasket on the cable in sequence.



3. Strip the cable. Put the support sleeve on the cable, and plug the stripped cable core into the metal terminal.




4. Clamp the terminal with a hydraulic clamp or a clamping machine. (Pay attention that the right size dies should be chosen.)



Qualified clamped cable data:

Crimp width(mm)	Crimp height(mm)	Pull-out force (N)	
(15.0)	11.27 11.5	≧3200N	



Australia: Alps Power Pty Ltd service@alpspower.com.au Telephone:+61 2 8005 6688

Europe: EFT-Systems GmbH service@eft-systems.de Telephone: +49 9352 8523999

+44(0)2037695998(UK) +34 91 060 22 67(ES) +39 0287 368364(IT)

USA: BYD US Service bboxusservice@byd.com Telephone:+1(833)338-8721

South Africa: AFRIPLUS ENERGY GROUP (PTY) Support@afriplusenergy.co.za Telephone:+27 21 140 3594

LATAM: BYD LATAM Service bboxservLATgrp@byd.com

BYD Global Service: bboxservice@byd.com Telephone: +86 755 89888888-47175

Service policy is subject to BYD's product warranty.

Economic Operator In Europe: BYD Smart Device Hungary kft. Brand: BYD Address: H-2071 paty, Szeng Jozsef ut 4.